

SAM4S

GCUBE

Thermal Receipt Printer



Top and Front Paper Exit

SAM4S delivers an affordable cube style POS printer that features all popular connection interfaces, including USB, Serial plus Ethernet, along with superior speed and reliability.

- Triple Interface Standard – USB+Serial+Ethernet
- Fast 250mm per Second Print Speed
- Compact Space-Saving Design
- Includes Serial and USB Cables and Power Supply
- LED Notifications
- NFC Function – NFC Allows Printer Set Up on an Android Device
- Compatible with Popular POS Software Applications

Contains Everything Necessary in the Carton – Including the Serial and USB Communication Cables



GCUBE Compact Thermal Receipt Printer



Spill-Proof Cabinet With Drop and Print Paper Loading



Optional Under Counter Bracket (Shown) and Wall Mount Bracket Available



Standard Cable Cover For Cable Management

Features

- Triple Interface Standard – USB+Serial+Ethernet
- Guillotine Style, Jam-Free Auto-Cutter
- Accepts 2-1/4" (58mm) 3-1/8" (80mm) Thermal Paper Rolls
- NFC Function – NFC Allows Printer Set Up on an Android Device
- Stores/Prints User Defined Graphic Logos, Coupons or Advertising Messages
- Stores Up to 255 Images (384) Kbytes in Non-Volatile Memory
- Easy-to-Use Utilities Simplify Loading Images and Watermarks
- Carton Includes: Gcube Printer, Starter Paper Roll, Serial Printer Cable, USB Cable, Cable Cover, Power Supply and Power Cord

Optional Devices / Upgrades

Upgrade your printer with these easy-to-add options:

- Under Counter Bracket
- Wall Mount Bracket
- Integrated Kitchen Bell



LED Printer Status Notification Such As Paper-End, Cover Open

Ports and Connectivity

Triple interface –Serial+Ethernet+USB and Cash Drawer port standard.

Specifications

Max. Print Speed – Mono 80mm:	250mm / 66 Lines per Second
Max. Print Speed – Mono 58mm:	150mm / 40 Lines per Second
Printing Method:	Direct Thermal
Resolution:	203 dpi
Characters Per Line – Font A:	42 (80mm) / 30 (58mm)
Characters Per Line – Font B:	56 (80mm) / 40 (58mm)
Characters Size – Font A:	12 x 24
Characters Size – Font B:	9 x 17
Paper Roll Type – Width:	80mm / 58mm
Maximum Diameter:	80mm
Paper Thickness:	0.06mm ~ 0.08mm
Auto Paper Cutting Method:	Guillotine Style, Jam-Free
Reliability – MCBF:	70,000,000 Lines
Reliability – Printhead Life:	≥ 150 KM
Reliability – Cutter Life:	1,500,000 Cuts
Character Set – Alphanumeric:	95
Character Set – International:	37
Character Set – Graphic:	128 x 31 Page: Code Pages for Popular Languages
Bar Code:	UPC-A / UPC-E / EAN8 / EAN13 / Code39 / Code93 / CODE128 / ITF / CODABAR / PDF417 / QR Code
Interpreter:	ESC/POS™ / Star™
Interface:	USB+Serial+Ethernet
Driver:	Windows® (Driver/OPOS) / MAC (CUPS) / iOS and Android SDK
Drawer Port:	Up to 2 Drawers (+24VDC) / Drawer Compulsion
Memory – Program Memory:	2 MB
Memory – Data Memory:	8 MB
Memory – Data Buffer:	64 KB
Power Supply:	AC 100 ~ 240 V, 50/60 Hz Adapter Included
Current/Power Usage:	2.5A / 60W
Operating Temperature:	40° ~ 114°F (5° ~ 45°C)
Operating Humidity:	10% ~ 85% RH (Non-Condensing)
Dimensions / Weight – Unit:	4-13/16"W x 4-13/16"D x 4-13/16"H
Dimensions / Weight – Shipping Carton:	9-1/2"L x 7-3/4"W x 8-1/4"H / 3.74 lbs.
Safety and EMI:	FCC Class A / CE / RoHS

